

K-FLEX® TITAN™ TAPE

REINFORCED FILM ADHESIVE TAPE



CHARACTERISTICS

Designed as a complementary product to K-FLEX® TITAN™ for sealing longitudinal seams and butt joints.

Can be torn laterally.

Ensures airtight layer.

Coated with special acrylic adhesive with extremely high moisture resistance.

Good adhesion to all smooth or slightly rough substrates.

Strong adhesive suitable for construction sites.

Outstanding ageing properties.

Free of solvents, emulsifiers and other emulsion additives.

PROPERTIES OF THE TAPE

Carrier: reinforced special polyethylene, film, semiflexible.

Adhesive: acrylic

Liner: repellent paper

K-FLEX® TITAN™ TAPE ▶ TECHNICAL DATA

Physical properties ▼	Value ▼	Test ▼
Thickness	0.01 in.	DIN EN 1942
Width	2 in.	
Length	328 ft.	
Elongation at break	150 %	DIN EN 14410
Tensile strength	1.75 lb/in	DIN EN 14410
Adhesion on steel	1.40 lb/in	DIN EN 1939
Temperature stability	-40 to +194 °F	
Application temperature	14 °F	

The K-FLEX® USA website contains the most recent version of all K-FLEX® USA literature. Please refer to the website for current versions of K-FLEX® USA literature at www.kflexusa.com

© K-FLEX® US_LEA_TITAN TAPE_V1_0619; K-FLEX® reserves the right to change data and technical requirements without notice.